



Intelligent *Surveillance System*

Auto - Tracking Module

High Resolution 530 TVL Wide Dynamic
27x / 30x / 36x Speed Dome Camera



 EverFocus®



Wide Dynamic Range



EPTZ3600



EPTZ3100



EPTZ2700

ÖZELLİKLER

	EPTZ3600	EPTZ3100	EPTZ2700
Görüntü Sensörü	1/4" Sony Ex-View Super HAD CCD	1/4" Verical DoubleDensity Interline CCD	1/4" Sony Ex-View Super HAD CCD
Sensör Sinyal Sistemi	PAL	PAL	PAL
Piksel Sayısı	752(H)x582(V)	752(H)x582(V)	752(H)x582(V)
Çözünürlük	Renkli 530TV Lines / SB 570 TV Lines	Renkli 520TV Lines / SB 570 TV Lines	Renkli 480TV Lines / SB 530 TV Lines
Zoom	36 X Optik Zoom - (10 X Dijital Zoom)	30 X Optik Zoom - (8 X Dijital Zoom)	27 X Optik Zoom - (10 X Dijital Zoom)
Işık Oranı	1,4 Lux / F 1,6 (50 IRE) Renkli: 0,01 Lux / F1,6 (50 IRE) Siyah Beyaz	0,4 Lux / F 1,6 (50 IRE) Renkli: 0,08 Lux / F1,6 (50 IRE) Siyah Beyaz	0,1 Lux / F 1,6 (50 IRE) Renkli: 0,005 Lux / F1,6 (50 IRE) Siyah Beyaz
Lens	3,4 mm - 122,4 mm arası	3,3 mm - 99,0 mm arası	3,25 mm - 88 mm arası
Video Çıkışı	1.0Vp-p 75 Ohm	1.0Vp-p 75 Ohm	1.0Vp-p 75 Ohm
Güç İhtiyacı	AC 24V	AC 24V	AC 24V
Çalışma Isısı	-40°C +50°C	-40°C +50°C	-40°C +50°C
S/N Oranı	50 dB'den fazla	50 dB'den fazla	50 dB'den fazla
BLC/True Day-Night	OSD Menü/Var	OSD Menü/Var	OSD Menü/Var
AWB/WDR	Digital/Var	Digital/Var	Digital/Var
Focus/Hareket Algılama	Auto Manuel/4 Bölge	Auto Manuel/4 Bölge	Auto Manuel/Var
Iris Kontrol	Auto Manuel	Auto Manuel	Auto Manuel
Bağlantı	RS - 485	RS - 485	RS - 485
Bağlantı Hızı	1200/2400/4800/9600 bps	1200/2400/4800/9600 bps	1200/2400/4800/9600 bps
Yatay Dönüş Açısı	360°	360°	360°
Dikey Dönüş Açısı	180°	180°	180°
Preset Pozisyonu	192 Nokta	192 Nokta	192 Nokta
Fan	Otomatik termostatlı	Otomatik termostatlı	Otomatik termostatlı
Speed Dome Address	0-255	0-255	0-255
Pan ve Tilt Hızları	Pan: 180°/sn Tilt: 90°/sn	Pan: 180°/sn Tilt: 90°/sn	Pan: 180°/sn Tilt: 90°/sn
Güç İhtiyacı	50 Watt	50 Watt	50 Watt

"Türkiye'nin Güvenlik Çözümü"