



Yazılım	WiFi	<p>SSID broadcast Number of SSIDs: 4 (2.4GHz)+4 (5GHz), supporting Chinese SSIDs Hide SSID function Wireless authentication methods: OPEN, WPA/WPA2-PSK Channel and channel bandwidth can be set Wireless MAC address filtering: supports whitelist (100) VLAN ID: The VLAN-ID range must be between 3 and 4094, where 0 indicates not enabled Spectrum navigation (5G priority) WiFi timed shutdown function User isolation: wireless network isolation, AP internal isolation Transmission power setting Limited number of wireless clients, supporting a maximum of 100 users Provides WIFI analysis functionality for the current environment</p>
	Network Fonksiyonları	<p>Ipv4 address: supports static addresses, obtains addresses from management servers, and obtains addresses from network administrators DHCP server: It can be either a built-in DHCP server or an external DHCP server Cloud Platform Server Firewall function PPPOE function: supports PPPOE dialing function</p>
	Cihaz Yönetimi	<p>Backup configuration information Restore Configuration Information Restore factory settings Reboot includes scheduled and immediate restarts Password modification Firmware upgrade, optional whether to restore factory settings after the upgrade is completed Time management includes system display time and time synchronization system log Fat and thin AP switching function</p>